

## MAIN TECHNICAL PARAMETERS 主要技术参数

型号	MODEL		2YJ8×10	2YJ6×8
工作质量 (不加载/加载)	Operating mass (without ballast/with ballast)	kg	8000/10000	6000/8000
碾压宽度	Rolling width	mm	1400	1400
前轮线载荷 (不加载/加载)	Front linear load (without ballast/with ballast)	N/cm	242/303	182/242
后轮线载荷 (不加载/加载)	Rear linear load (without ballast/with ballast)	N/cm	343/429	257/343
行驶速度 (前进/后退)	Travel speed (forward/reverse)	Km/h		
一速	1st gear		2.62	2.62
二速	2nd gear		5.18	5.18
三速	3rd gear		10.30	10.30
爬坡能力	Gradeability	%	20	20
转弯半径 (内侧/外侧)	Turning radius (inside/outside)	mm	5050/6450	5050/6450
外观尺寸 (长×宽×高)	Overall dimension (L×W×H)	mm	4400×1770×2620	4380×1710×2560
轴距	Wheelbase	mm	3150	3150
最小离地间隙	Ground clearance	mm	320	320
发动机型号	Diesel engine model		SN4102BY	498BG
额定功率/转速	Rated power/Rotational speed	kW/r/min	55.5kW/2200r/min	36kW/2000r/min
最大扭矩/转速	Maximum torque/rotational speed	N.m/rpm	250N.m/1500rpm	205N.m/1800rpm
电压	Electrical voltage	V	12/24DC	12DC
燃油箱容积	Fuel tank capacity	liter	114	120
水箱容积	Water tank capacity	liter	435	300
液压油箱容积	Hydraulic tank capacity	liter	50	50
驾驶室	Cabin		Steel sealed cabin over driving seat	Steel sealed cabin over driving seat
颜色	Color		Yellow/white	Yellow/white

本厂产品随技术进步不断改进，样本所列参数和结构特性与实物可能会存在差异之处。我们将不断更新数据。如有不足之处，请您谅解。

Our products will continuously improved with the progressing of the technique. So please indicate the difference between the listed parameters in the sample shit and structure features and the objects when ordering.



一拖国际经济贸易有限公司  
YTO INTERNATIONAL, LTD